





# SERIES-3000

#### APPLICATIONS:

- Houses of Worship
- LIVE/CONCERT SOUND FILLS
- CLUBS/LOUNGES
- THEATERS/LIVE VENUES

## DESCRIPTION:

#### **Purpose-Designed**

The 3000-series from Sound Bridge are 2-way, full-range devices with integral passive crossover networks. The series was designed specifically to compliment 7000-series systems in a variety of uses for both the concert/live sound and the permanent installation markets.

3000-series enclosures supplement 7000-series line array systems by serving as front-fills, under-balcony speakers, delay ring speakers, and in many other capacities. 3000-series enclosures also work well in smaller, lower-ceiling rooms and as distributed systems.

#### Horizontal Configuration, High Output

The 3212HTH is a horizontally-configured enclosure that is well-suited for stage-front and under-balcony situations where high-output is needed. With dual 12" drivers, the 3212HTH delivers 134dB peak output with low-frequency extension below 50Hz. The internal crossover is switchable, allowing for biamp (with dual-drive option to run the 12" drivers independently) or full-range passive operation. The cabinet includes integral steel rigging points, allowing easy suspension with the use of standard shouldered eyebolts.

#### Durability

3000-Series enclosures are finished in 100% solid tour-grade Duracoat<sup>™</sup>. This long-life surface is highly abrasion resistant so boxes stay new-looking, even in rigorous applications.

#### **Custom Colors**

3000-series enclosures are available in custom colors to match the décor of the venue they are being installed in. Practically any color is possible, based on matching a customer-provided sample or Pantone color.

### SPECIFICATIONS:

#### Horizontal Dispersion: 110-degrees Vertical Dispersion: 70-degrees

Frequency Response: 50Hz -to- 18kHz, +/-3dB

Max SPL: 128dB SPL Cont., 134dB SPL Peak

LF Drive Unit(s): (2) 12" Cone Driver HF Drive Unit(s): (1) 1" Titanium HF

<u>Sensitivity</u>: 100dB 1w/1m <u>Power Handling</u>: 600w (Cont.), 1200w (Peak) <u>Impedance</u>: 4-Ohms

<u>Cabinet Construction</u>: 13-Ply 3/4" High-Quality Baltic Birch plywood with dado joints, recessed baffle and 16-guage front-perforated steel grill <u>Cabinet Finish</u>: Tour-Grade Duracoat<sup>™</sup> <u>Connections</u>: (2) Neutrik NL-4 Speakon

Dimensions (Imperial): 19.8" x 37" x 19" Dimensions (Metric): 50.3cm x 94cm x 48.3cm Weight: 89lbs (40.5kgs)

<u>Available Accessories</u>: EB-3816 3/8"-16 shouldered eyebolt for rigging