

FLYING HIGH-PERFORMANCE SUBWOOFER



APPLICATIONS:

- HOUSES OF WORSHIP
- LIVE/CONCERT SOUND
- CORPORATE RENTAL HOUSES
- THEATERS/LIVE VENUES
- **CLUBS/LOUNGES**

DESCRIPTION:

The 7118SWX-F is a high-performance; high-output subwoofer system designed to compliment XYON™ line array systems in a variety of permanently-installed and live sound reinforcement applications.

The 7118SWX-F utilizes advanced components and technology to attain the highest performance levels. The use of a highly-efficient and high power-handling, yet lightweight, Neodymium driver results in massive output relative to size and weight.

The 7118SWX-F version is intended for flown applications and includes the integrated XYON™ Z-MAX modular rigging system. 7118SWX-F enclosures may be transported in two's or four's on DL-7118 Dolly Boards, and padded transports covers are available.

Recommended amp and cabling configurations are available, as well as DSP processor settings for many commonly used system controllers.

The 7118SWX-F is the perfect companion subwoofer for XYON™ 7108XY line array system. 7118SWX-F subwoofers may be flown at the top of 7108XY arrays or in separate bass hangs.



SPECIFICATIONS:

Frequency Response: 45Hz -to- 200Hz, +/-3dB

Max SPL: 135dB SPL

LF Drive Unit(s): (1) Neodymium 18" Cone

LF: Sensitivity: 99dB 1w/1m

LF Power Handling: 1000w (AES), 4000w (Peak)

LF Impedance: 8-Ohms

Cabinet Construction: 18mm 13-Ply Baltic Birch, High

Tensile UHMW Composite

Cabinet Finish: Tour-Grade Duracoat™

Hardware: XYON Z-MAX modular rigging system Connections: (2) Neutrik NL-4 Speakon

Dimensions (Imperial): 21.5" x 26.75" x 31" Dimensions (Metric): 54.6cm x 68cm x 78.7cm

Weight: 98lbs (44.5kgs)

Available Accessories: FB-7108/7118 Fly Bar, DL-7118 Dolly Board (up to 4 units), CV-7118 Padded Transport Cover (2 units on DL)