

Application

The 3118SW is an extended low-range system designed for a wide variety of speech and music applications, such as clubs, churches, or concert settings.

Description

The 3118SW is trapezoidal in shape with a curved front, facilitating cluster or stacked applications. It is designed to be utilized as a low frequency enhancement to the 3000 series full-range speakers.

Cabinetry

The cabinet design uses a 13 ply 3/4 high quality baltic birch plywood with dado joints, recessed baffle and a 16 gauge front perforated grill for long lasting durability. The baffle is cut from 1" MDF to enhance acoustical properties and to give the components a rigid interface. Two Neutrik Speakon connectors and Neutrik parallel 1/4" jacks are installed on all speakers in the 3000 series.

Covering Options

The cabinet comes coated in black Duracoat. It is also available in white Duracoat and a natural birch finish. Please refer to price sheet for upgrade pricing.

Transducers

The cabinet is loaded with a 18" cast aluminum low frequency driver in a tuned vented enclosure. The cabinet is tuned by means of a vented port set at the optimum frequency.

Specifications

Frequency Response:	35hz-800hz
Power Handling:	450w (cont.)
Sensitivity (1 watt/meter):	99dB
Nominal Dispersion:	N/A
Impedance:	8 Ohms

Transducer Components

Low Frequency:	18" woofer
High Frequency:	None

Audio Input Connections: Two Neutrik Speakon connectors and two parallel jacks.

Enclosure:	Vented
Crossover:	None
High Frequency Protection:	N/A
Steel Pole Mount:	Yes, Inverted

Physical

Dimensions (H x W x D):	32" x 24.8" x 24" (81cm x 63cm x 61cm)
Weight:	78 lbs./35.5 Kg

Warranty Information

The 3000 Series high definition speakers feature a 10 year warranty. Please refer to the warranty information card shipped with all Sound Bridge speaker products.

