



SERIES-3000

APPLICATIONS:

- ▶ - HOUSES OF WORSHIP
- ▶ - LIVE/CONCERT SOUND
- ▶ - CLUBS/LOUNGES
- ▶ - THEATERS/LIVE VENUES
- ▶ - CORPORATE RENTAL HOUSES

DESCRIPTION:

Purpose-Designed

The 3000-series of floor monitors from Sound Bridge are high-performance 2-way enclosures with switchable passive crossover networks, which allow operation in either biamp or full-range passive modes. The series was designed to be the best solution when the extreme high power and output capacity of the 7000-series SLICE™ floor monitors is not required.

Horizontal Configuration, High Output

The 3112WL enclosure is horizontally-configured to provide maximum performance in a sleek low-profile package that won't clutter up appearances on the stage. The 3112WL is loaded with premium components to deliver best-in-class performance; capable of 130dB peak output and low-frequency extension below 60Hz.

Durability

3000-Series enclosures are finished in 100% solid tour-grade Duracoat™. This long-life surface is highly abrasion resistant so boxes stay new-looking, even in rigorous applications.

Custom Colors

3000-series enclosures are available in custom colors to match the décor of the venue they are being installed in. Practically any color is possible, based on matching a customer-provided sample or Pantone color.

SPECIFICATIONS:

Horizontal Dispersion: 110-degrees

Vertical Dispersion: 70-degrees

Frequency Response: 60Hz -to- 18kHz, +/-3dB

Max SPL: 124dB SPL Cont., 130dB SPL Peak

LF Drive Unit(s): (1) 12" Cone Driver

HF Drive Unit(s): (1) 1" Titanium HF

Sensitivity: 98dB 1w/1m

Power Handling: 450w (Cont.), 900w (Peak)

Impedance: 8-Ohms

Cabinet Construction: 13-Ply 3/4" High-Quality Baltic Birch plywood with dado joints, recessed baffle and 16-gauge front-perforated steel grill

Cabinet Finish: Tour-Grade Duracoat™

Connections: (2) Neutrik NL-4 Speakon

Dimensions (Imperial): 14.75" x 26" x 17"

Dimensions (Metric): 37.5cm x 66cm x 43.2cm

Weight: 53lbs (24.1kgs)