



DESCRIPTION:

The 7208XY is a compact line array system designed for a wide variety of permanently-installed and live sound reinforcement applications. Like all XYON™ Series systems, the 7208XY utilizes advanced technology to attain the highest performance levels.

7208XY units are configured as alternating upright and inverted units, paired to create a low-frequency horn termed QUAD-One™. By focusing all four LF drivers at the same quadrant of a sphere, greater directivity and increased sensitivity is realized. Whereas typical line array systems require very large arrays to achieve this level of directivity and output, XYON™ does so with as few as two elements.

In the Mid and High Frequency bands, the XYON™ Series utilizes Neodymium Mid/HF EXO drivers on patented Q-Drive™ WaveShaper horns. One device, which excels at eliminating crossover and phase/time anomalies, reproduces all frequencies from critical vocal intelligibility range up through upper-harmonics and to top of the frequency band. This feature, combined with exceptional transient response, results in a high fidelity vocal and upper-mid response that sounds more natural than the traditional "PA sound". Vocals, acoustic instruments and snare drums are crisp and clear and mixes never sound "crowded" or "muddy".

Elements are configurable for flown, as well as ground-stack applications. All models are wired for biamp operation, and optional triamp configuration with LF pass-through is available. In 2-way wiring configurations, it is possible to power four modules using just one power amplifier. Recommended amp and cabling configurations are available, as well as DSP processor settings for many commonly used system controllers. XY-On™ Space Shape prediction and control software is available to calculate optimum array angles for precise energy placement in audience areas. Additionally, GLL data is available for use with EASE Focus modeling software.

The 7208XY is recommended to be used with companion 7000-Series Subwoofers, such as the 7218SWX, the 7218SWX-F and the 7221SWX. 7208XY modules may be flown under 7218SWX-F Subwoofers.



APPLICATIONS:

- ▶ - HOUSES OF WORSHIP
- ▶ - REGIONAL TOURING COMPANIES
- ▶ - CORPORATE RENTAL HOUSES
- ▶ - THEATERS/LIVE VENUES
- ▶ - CLUBS/LOUNGES

SPECIFICATIONS:

Horizontal Dispersion: Interchangeable 80-degrees or 120-degrees

Vertical Dispersion: 10-degrees (1 unit)

Frequency Response: 68Hz -to- 22kHz, +/-3dB

Max SPL: 137.7dB SPL (1 unit), 149.7dB (4 units)

LF Drive Unit(s): (2) Neodymium 8" Cone

LF Sensitivity: 106dB 1w/1m

LF Power Handling: 400w (AES), 1600w (Peak)

LF Impedance: 8-Ohms

HF Drive Unit(s): (1) Neodymium MF/HF EXO

HF Sensitivity: 118dB 1w/1m

HF Power Handling: 250w (AES), 1000w (Peak)

HF Impedance: 16-Ohms

Cabinet Construction: 18mm 13-Ply Baltic Birch, High Tensile UHMW Composite

Cabinet Finish: Tour-Grade Duracoat™

Hardware: XYON Z-MAX modular rigging system

Connections: (2) Neutrik NL-4 Speakon

Dimensions (Imperial): 8.75" x 38.75" x 20.25"

Dimensions (Metric): 22.2cm x 98.4cm x 51.4cm

Weight: 86lbs (39kgs)

Available Accessories: FB-7208S Short Fly Bar (up to 8 units), FB-7208/7218L Long Fly Bar (up to 16 units), DL-7208 Dolly Board, CV-7208 Padded Transport Cover